

הנגדות טיפוסית (ohm/1000m)	שטח חתך (mm ²)	קוטר (in)	קוטר (mm)	AWG
3420	0.0050	.	0.08	40
2700	0.0064	.	0.09	39
2190	0.0078	0.0040	0.10	38
1810	0.0095	0.0045	0.11	37
1300	0.013	0.005	0.13	36
1120	0.015	0.0056	0.14	35
844	0.020	0.0063	0.16	34
676	0.026	0.0071	0.18	33
547	0.031	0.008	0.20	32
351	0.049	0.01	0.25	30
232.0	0.08	0.013	0.33	28
178	0.096	0.018	0.36	27
137	0.13	0.016	0.41	26
108	0.16	0.018	0.45	25
87.5	0.20	0.02	0.51	24
51.7	0.33	0.025	0.64	22
34.1	0.50	0.032	0.81	20
21.9	0.82	0.04	1.02	18
13.0	1.3	0.051	1.29	16
8.54	2.0	0.064	1.63	14
6.76	2.6	0.072	1.80	13
5.4	3.3	0.081	2.05	12
3.4	5.26	0.10	2.59	10
2.2	8.30	0.13	3.25	8
1.5	13.30	0.17	4.115	6
0.8	21.15	0.20	5.189	4
0.5	33.62	0.26	6.543	2
0.4	42.41	0.29	7.348	1
0.31	53.49	0.33	8.252	0
0.25	67.43	0.37	9.266	00 (2/0)
0.2	85.01	0.41	10.40	000 (3/0)
0.16	107.22	0.46	11.684	0000 (4/0)